



Stackable AIO

THREE-PHASE **HYBRID/AC**



FLEXIBLE APPLICATION

- Built-in 63A bypass for full house backup.
- 3 MPPTs, 20A per string.
- PV min. voltage of 120V and min. battery voltage of 80V.



EASY INSTALLATION

- Integrated configuration, plug and play set-up.
- Designed for single-person installation.



SAFE AND DURABLE

- Integrating active and passive safety.
- Intelligent AFCI function.
- IP66 and type II DC/AC surge protection.



REMOTE MONITORING

- Monitor your system remotely via smartphone App or Web portal.
- Ready for AI and VPP Apps.



Advanced System Monitoring
with **FoxCloud V2.0**



Stackable AIO is the latest generation of an integrated residential energy storage system, modular designed to meet various installation scenarios.

5kW ...>> 15kW



For more information about the Fox ESS range, visit:
www.fox-ess.com

TECHNICAL SPECIFICATIONS

MODEL	PQ3-5.0-M	PQ3-6.0-M	PQ3-8.0-M	PQ3-10.0-M	PQ3-12.0-M	PQ3-15.0-M
PV INPUT						
Max. Array Power[W]	11000	14000	18000	20000	24000	30000
Max. Input Power [W]	11000	13200	17600	20000	24000	30000
Max. Input Voltage [V]	1000 [1]					
Nominal Operating Voltage [V]	620					
Max. MPPT Input Current [A]	20/20/20					
Max. MPPT Short-Circuit Current [A]	25/25/25					
Max. MPPT Input Power [W]	10000/10000/10000					
Min. Operating Input Voltage [V]	90 [2]					
MPPT Voltage Range [V]	120 ~ 950					
Start-Up Input Voltage [V]	140					
MPPT Voltage Range (Full Load) [V]	120 ~ 850	120 ~ 850	140 ~ 850	175 ~ 850	210 ~ 850	263 ~ 850
No. of MPP Trackers	3					
Strings per MPP Tracker	1+1+1					
Max. Inverter Backfeed Current to the Array	0					
BATTERY CONNECTION						
Battery Type	Lithium-Ion battery (LFP)					
Battery Voltage [V]	80 ~ 500					
Min. Operating Battery Voltage [V]	85					
Min. Battery Voltage @ Full AC Load [V]	108	125	160	210	250	310
Max. Battery Charge Power [W]	6000	7200	9600	12000	14400	15000
Max. Battery Discharge Power [W]	5000	6000	8000	10000	12000	15000
Max. Charge/Discharge Current [A]	50					
Communication Interface	CAN					
AC OUTPUT						
Nominal Output Power [W]	5000	6000	8000	10000	12000	15000
Max. Apparent Output Power [VA]	5500	6600	8800	11000	13200	16500
Rated Grid Voltage (AC Voltage Range) [V]	400/230; 380/220, 3L/N/PE					
Rated Grid Frequency [Hz]	50/60, ±5					
Rated Output Current (Per Phase) [A]	7.6	9.1	12.1	15.2	18.2	22.7
Max. Output Current (Per Phase) [A]	8.3	10.0	13.3	16.7	20.0	25.0
Power Factor	1 (Adjustable from 0.8 leading to 0.8 lagging)					
THDI [%]	<3 @rated power					
AC INPUT						
Max. Input Power [VA]	43470					
Rated Grid Voltage [V]	400/230; 380/220, 3L/N/PE					
Rated Grid Frequency [Hz]	50/60, ±5					
Max. Input Current (Per Phase) [A]	63					
EPS OUTPUT(ON GRID MODE)						
Max. Output Power For Backup Load (Per Phase) [W]	43470					
Max. Output Current For Backup Load [A]	3*63					
EPS OUTPUT(OFF GRID MODE)						
Max. Apparent Output Power [VA]	5000	6000	8000	10000	12000	15000
Peak Apparent Output Power (60s) [VA]	6000	7200	9600	12000	14400	15000
Rated Output Voltage [V]	400/230; 3L/N/PE					
Rated Grid Frequency [Hz]	50/60					
Max. Continuous Current (Per Phase) [A]	7.2	8.7	11.6	14.5	17.4	21.7
Max. Unbalanced Load Power (Per Phase) [kW]	1.6	2.0	2.6	3.3	4.0	5.0
Step-Down Start	YES					
EPS Overload Automatic Recovery Time	Try 3 times(15s) everytime will alarm a fault, after 3 failures, stop the recovery logic, clients need to clear the fault manually.					
Power Factor	1 (Adjustable from 0.8 leading to 0.8 lagging)					
Parallel Operation	Yes @max10PCS					
Switch Time (Single Device) [ms]	<20					
THDV [%]	<3 @rated power					
EFFICIENCY						
MPPT Efficiency [%]	99.90					
Max. Efficiency [%]	97.80	97.80	97.90	97.90	97.90	97.90
European Efficiency [%]	97.00	97.00	97.10	97.30	97.50	97.50
Max. Battery Charge Efficiency (PV to BAT) (@ Full Load) [%]	97.00	97.10	97.20	97.40	97.50	97.60
Max. Battery Discharge Efficiency (BAT to AC) (@ Full Load) [%]	97.00	97.10	97.20	97.20	97.20	97.20

TECHNICAL SPECIFICATIONS

MODEL	PQ3-5.0-M	PQ3-6.0-M	PQ3-8.0-M	PQ3-10.0-M	PQ3-12.0-M	PQ3-15.0-M
PROTECTION						
PV Reverse Polarity Protection				YES		
Battery Reverse Protection				YES		
Anti-Islanding Protection				YES		
Output Short Protection				YES		
Leakage Current Protection				YES		
Insulation Resistor Detection				YES		
Overvoltage Category			III (AC Side), II (DC Side)			
Reverse Connect Protection				YES		
Overcurrent Protection/Overtemperature Protection				YES		
DC/AC Surge Protection			Type II (PV)/Type II (AC)			
AFCI Protection				Optional		
DC Switch				YES		
GENERAL DATA						
Dimensions (W*H*D) [mm]			570*420*380 (Inverter)			
Dimensions of Packing (W*H*D) [mm]			654*538*464 (Inverter)			
Net Weight [kg]			40.5 (Inverter)			
Gross Weight [kg]			45.0 (Inverter)			
Installation			Floor-mounted			
Operating Temperature Range [°C]			-25 ~ +60 (Derating at 45)			
Storage Temperature [°C]			-40 ~ +70			
Storage/Operation Relative Humidity [%]			0 ~ 100 (No condensation)			
Altitude [m]			<4000 @ Derating Exceeding 3000			
Protection Class			I			
Ingress Protection			IP66 (For Outdoor Use)			
Standby Consumption [W]			200 for Work, 15 for Switch Off			
Idle Mode			YES			
Cooling	Natural	Natural	Natural	Natural	FAN Cooling	FAN Cooling
Noise Level [dB]	<40	<40	<40	<40	<55	<55
Inverter Topology			Non-Isolated			
Monitoring Module (Integrated)			WIFI, LAN, 4G			
Communication Interface		Meter, WIFI/4G (Optional), Bluetooth, DRM, Ethernet, USB, BMS (CAN), RS485, Ripple Control, SG Ready, Dry Contact*2				
Display			LED, LCD, App, Website			
Button			Capacitive Touch Sensor			
Buzzer			1, Inside (EPS & Earth Fault)			
STANDARD						
Safety			EN/IEC62109-1, EN/IEC62109-2			
EMC		IEC 61000-6-1, IEC 61000-6-2, IEC 61000-6-3, IEC61000-4-2/3/4/5/6/8				
Certification		AS4777.2-2020, VDE-AR-N 4105, VDE0126-1-1, G98, EN50549-1, CEI 0-21, IEC62116, IEC61727, IEC61683				

[1] For 1000V system, PV maximum operating voltage is 950V.

[2] The starting working voltage of the power supply is 90V.

TECHNICAL SPECIFICATIONS

MODEL	TQ5000-S -L2	TQ5000-S -L3	TQ5000-S -L4	TQ5000-S -L5	TQ5000-S -L6
ELECTRICAL CHARACTERISTICS					
Battery Type	LFP (LiFePO ₄)				
Battery Module	2*TQ5000-S	3*TQ5000-S	4*TQ5000-S	5*TQ5000-S	6*TQ5000-S
Nominal Capacity [kWh]	9.84	14.76	19.68	24.60	29.52
Nominal Voltage [V]	128	192	256	320	384
Operating Voltage [V]	116 ~ 146	174 ~ 219	232 ~ 292	290 ~ 365	348 ~ 438
Recommend Discharge Current [A]	38.5				
Max. Charge/Discharge Current [A] ^{*1}	50				
Peak Discharge Current [A]	65 @60sec				
Battery Pack Round-Trip Efficiency [%]	>95				
Depth of Discharge [%]	90				
Communication	CAN				
Display	LED*1				
Scalability	Max. 6 Modules in Series				
OPERATING CONDITIONS					
Installation Location	Outdoor/ Indoor				
Operating Temperature [°C]	Charge: 0 ~ 55, Discharge: -10 ~ 55				
Operating Temperature [°C] (warm up function on, optional)	Charge: -25 ~ 55, Discharge: -25 ~ 55				
Storage Temperature [°C]	-10 ~ 50				
Cooling Method	Natural Convection				
Humidity [%]	5 ~ 95 (No Condensation)				
Altitude [m]	Max. 3,000				
PROTECTION					
Fire Protection Function	YES				
MECHANICAL CHARACTERISTICS					
Dimensions (W*H*D) [mm]	570*375*380	570*510*380	570*645*380	570*780*380	570*915*380
Weight [kg]	97.2	140.7	184.2	227.7	271.2
CERTIFICATES					
Safety	IEC 62619				
EMC	IEC 61000-6-1/2/3/4				
Transportation	UN38.3				
Ingress Protection	IP65				

*1, The current is affected by temperature ,cell voltage and SOC.